

DIGITUS® Fiber Optic 2 mm shrink splice protection, 45 mm

AL-SK6

EAN 4016032349297



Fiber Optic 2 mm Shrink Splice Protection 45 mm 1 mm stainless steel wire, 1 pc = 1 tray w 100 pcs.

This Fiber Optic shrink splice protection is ideal to protect the splice from 2 fibers after the splicing. It shrinks to the fiber when you heat him.

- Keeps optical transmission properties of optical fiber
- Provides strength and protection to optical fiber splices
- Easy usage, avoid damages to the optical fiber
- Operating temperature: -45 °C up to +100 °C
- Packaging: 100 pcs

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	600	26.50	37.00	27.00	48.00	47,952.00
Packaging Unit Inside	12	0.53	7.00	18.50	27.00	3,496.50
Packaging Unit Single	1	0.04	2.00	5.50	6.00	66.00
Net single without Packaging	1	0.04	0.00	0.00	0.00	0.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com